

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** NOW Color HG-SDM
- **Article number:**
4000354200, 4000354201, 4000354202, 4000354204, 4000354205, 4000354206, 4000354207, 4000354208, 4000354209, 4000354210, 4000354211, 4000354212, 4000354213
- **Application of the substance / the preparation:** Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Nordwest Handel AG
Berliner Str. 26 - 36
D-58135 Hagen

Phone: +49 (0)2331/4610
Fax: +49 (0)2331/461389
- **Further information obtainable from:** see above
- **Emergency telephone number:**
Beratungsstelle bei Vergiftungen, Mainz
Tel. 0049 (0) 6131 / 19240

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Warning! Pressurized container.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
F+ Extremely flammable
- **Risk phrases:**
12 Extremely flammable.

Trade name: NOW Color HG-SDM

(Contd. of page 1)

66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

• Safety phrases:

2 Keep out of the reach of children.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe fumes/aerosol.
51 Use only in well-ventilated areas.
56 Dispose of this material and its container to hazardous or special waste collection point.
60 This material and its container must be disposed of as hazardous waste.

• Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Buildup of explosive mixtures possible without sufficient ventilation.

• Classification in accordance with Directive 75/324/EEC: Extremely flammable

• Other hazards

• Results of PBT and vPvB assessment

• **PBT:** Not applicable.
• **vPvB:** Not applicable.

3 Composition/information on ingredients

• Chemical characterization: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	n-butyl acetate R10-66-67 ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane ⚠ F+ R12 ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 02-2119752542-40-0000	acetone ⚠ Xi R36; ⚠ F R11 R66-67 ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane ⚠ F+ R12 ⚠ Flam. Gas 1, H220; ⚠ Press. Gas, H280	10-25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate ⚠ Xi R36; ⚠ F R11 R66-67 ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2,5-10%

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

• Description of first aid measures

• **After inhalation:** Supply fresh air; consult doctor in case of complaints.
• **After skin contact:** Generally the product does not irritate the skin.
• **After eye contact:** Rinse opened eye for several minutes under running water.
• **Information for doctor:**
• **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Trade name: NOW Color HG-SDM

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

IOELV 1210 mg/m³, 500 ppm

(Contd. on page 4)

Trade name: NOW Color HG-SDM

(Contd. of page 3)

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
 Filter AX
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**
 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
 Nitrile rubber, NBR
 Fluorocarbon rubber (Viton)
 Recommended thickness of the material: $\geq 0,6$ mm
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Light weight protective clothing

9 Physical and chemical properties

• Information on basic physical and chemical properties

• General Information

• Appearance:

- | | |
|--------------------|-----------------|
| Form: | Aerosol |
| Colour: | Various colours |
| • Odour: | Solvent-like |
| • Odour threshold: | Not determined. |

- | | |
|-------------|-----------------|
| • pH-value: | Not determined. |
|-------------|-----------------|

• Change in condition

- | | |
|------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | -44°C |

- | | |
|----------------|-------|
| • Flash point: | -97°C |
|----------------|-------|

- | | |
|----------------------------------|-----------------|
| • Flammability (solid, gaseous): | Not applicable. |
|----------------------------------|-----------------|

- | | |
|-------------------------|-------|
| • Ignition temperature: | 365°C |
|-------------------------|-------|

- | | |
|------------------------------|-----------------|
| • Decomposition temperature: | Not determined. |
|------------------------------|-----------------|

- | | |
|------------------|------------------------------|
| • Self-igniting: | Product is not selfigniting. |
|------------------|------------------------------|

- | | |
|------------------------|---|
| • Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
|------------------------|---|

(Contd. on page 5)

Trade name: NOW Color HG-SDM

(Contd. of page 4)

· Explosion limits:	
Lower:	1,2 Vol %
Upper:	13,0 Vol %
· Vapour pressure at 20°C:	8300 hPa
· Density at 20°C:	0,75945 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Segregation coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	85,0 %
VOC (EC)	85,00 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritating effect possible.
- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 6)

Trade name: NOW Color HG-SDM



(Contd. of page 5)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste disposal key:** 150104
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · ADR, IMDG, IATA	UN1950
· UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· Transport hazard class(es) · ADR	
	
· Class · Label	2 5F Gases. 2.1
· IMDG, IATA	
	
· Class · Label	2.1 2.1
· Packing group · ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Gases. - F-D,S-U
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Tunnel restriction code	D
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

Trade name: NOW Color HG-SDM

(Contd. of page 6)

15 Regulatory information

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

R10 Flammable.
R11 Highly flammable.
R12 Extremely flammable.
R36 Irritating to eyes.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:**

NORDWEST Service Center
Tel.: +49 (0)2331/4614500
Fax: +49 (0)2331/4614549
Email: service-center@nordwest.com

- **Contact:** Mr. Otling / Dipl. Kfm. Mr. Prasuhn

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
VOC: Volatile Organic Compounds (USA, EU)

- *** Data compared to the previous version altered.**